

The European designed COSMO Bully VH Series Rotary Hoes have a multi speed gearbox that is rated 50 to 90hp.

The main frame is a robust and rigid construction with box section reinforcing and the side gears are sealed via a gasket creating an oil bath.

The COSMO Bully VH Series produces a super fine finish. The spring loaded tailgate keeps soil inside and in contact with the blades until it is well pulverised.

The multi speed gearbox allows the operator to customise the rotor speed. The rotor design, Ø 521mm from blade to blade, allows a large amount of soil to be worked without clogging up the chamber.

The speed blade configuration, a design where six (6) L shaped blades (per flange) are slightly staggered, reduces the tractor horsepower required.



The COSMO Bully VH Series can operate all day, every day, in demanding soil conditions and is suitable for a range of commercial horticultural and gardening applications including nurseries, vineyards and orchards.

Code	TBVH60	TBVH70	TBVH80
Description	Bully VH60 Rotary Hoe	Bully VH70 Rotary Hoe	Bully VH80 Rotary Hoe
Side transmission	Gear drive		
Gearbox	90hp, 540rpm, multi speed (1000rpm option)		
PTO shaft/clutch	Series 6 with 200mm (8") friction (slip) clutch		
Skids	Height adjustable		
Finish	Powder coated		
Rotor diameter (mm)	521		
Rotor speed (rpm)	191 - 240 at 540rpm   248 at 1000rpm		
No. of rotor flanges	6	7	8
No. of blades p/flange	6	6	6
Total no. of blades	36	42	48
Blades	Square/L shaped standard   Curved/speed on request		
Linkage	Category 2		
Guarding	Standard with CE guards		
Overall width (mm)	1705	1945	2185
Working width (mm)	1540	1780	2020
Working depth (mm)	225		
Tractor range (hp)	50 - 90	60 - 90	70 - 90
Weight (kg)	580	620	665

#### Parts

3029	VH/UHH square/L shaped blade (right)
1374	VH/UHH square/L shaped blade (left)
23160	VH/UHH curved/speed blade (right)
23159	VH/UHH curved/speed blade (left)